

760 Multi-Purpose Spray Adhesive

1 - Description

Akfix 760 is a general-purpose product that provides strong adhesion thanks to its special formula. It has a wide range of use in home and office applications with its practical use. Provides a strong and permanent bond.

2 - Properties

- Adaptability to many porous and non-porous surfaces,
- Does not leave marks on surfaces,
- Easy to use,
- Fast and strong adhesion.

3 – Application Areas

It is used for bonding to many surfaces such as;

-Paper	-Felt	-Glass
-Cardboard	-Textile	-Metal
-Polyester	-Leather	-Most plastic
-Collage	-Filter Paper	-Tire
-Foils	-Wood	-Carpet

4 – Packaging and Shelf Life

Packaging	400 ml , 500 ml
Shelf Life	12 months
Storage Conditions	Store between 8°C and 21°C

5 – Technical Data

Property	Value
Form	Liquid Aerosol
Appearance	Transparent
Specific gravity	0,78 ± 0,02 gr/cm ³
Odor	Characteristic
Flash Point	N/A

6 - Directions for Use

- The surfaces to be applied must be dry, clean, and free from dust and oil.
- The can should be shaken vigorously before and during application.
- Apply at a 45° angle from a 15-20 cm distance.
- For strong adhesion, at least one of the surfaces to which the adhesive is applied must be porous.
- The adhesive is applied to both surfaces. The bonding process is carried out after waiting for 1 minute and pressed flat.
- Curing time may vary depending on the amount of adhesive applied, humidity and ambient temperature.
- To prevent the can from clogging after use, turn the can upside down and press the trigger several times to release the propellant gas and clean the beak.

7 - Remarks & Restrictions

- Smoking should not be done during work and the environment should be ventilated.
- It should not be sprayed on extremely hot parts.
- Before applying to sensitive surfaces, a compatibility test should be performed on an invisible part of the parts.
- Do not spray on naked flames or glowing objects.
- It should be kept away from flammable materials.
- The tube is under pressure; it should not be exposed to direct sunlight and temperatures above 50°C.
- Should be kept away from children
- Use only in well-ventilated areas
- Use gloves while working.

8 - Disclaimer

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.