



# PVC FLOORING ADHESIVE

**PVC Flooring Adhesive** is a one part, water borne acrylic based adhesive that is used for adhesion of PVC/Vinyl floorings and tiles, heterogeneous PVC, expanded vinyl, semi-flexible floor tiles and felt-backed carpets to the floor.

## FEATURES & BENEFITS

- Single component, no mixing required
- Solvent-free, very low emissions
- Easy to apply
- Long open time
- Strong initial adhesion power
- Stable and elastic adhesive
- Suitable for use of wheelchair and rubber-wheeled vehicle traffic
- Suitable for installation on under-floor heating systems

## APPLICATION AREAS

- Concrete, sand/cement screeds
- Smoothened sub-floors
- Subfloors composed of wood materials
- For Interior use only
- Use only horizontal surface

## INSTRUCTIONS

- Before application, be sure that joint surfaces are clean, smooth, dry and free of all contamination.
- If necessary, substrate should be consolidated with screed for repairing cracks and should be applied primer in order to reduce consumption and obtain a homogenously balanced absorptive sub-floor.
- Pour the adhesive on the floor and apply with a notched trowel in one smooth layer on the whole application area. Place and fix the floor covering material on the surface after 5-10 minutes
- Place the flooring materials while the adhesive is wet and capable of holding the material.



### Consumption (approx.)

Type of Floor Coverings	Types of notched trowel	Consumption per m <sup>2</sup>
Smooth ridge and very thin floor coverings on the all of the floor surface	A4 or roll	230 g
Smooth ridge floor coverings	A2	250-300 g
Slightly rough ridge, rubber floor coverings	B1	320-350 g
Rough ridge floor coverings	B2	400-510 g

### RESTRICTIONS;

- Avoid application below +5 °C and above +35 °C.
- Do not apply on damp substrates or those subject to possible rising damp.

### STORAGE AND SHELF LIFE;

- It should be protected from water, frost and adverse air conditions.
- Opened products should be closed immediately and consumed first.
- Shelf life is maximum 12 months conditional to complying with the mentioned storage conditions.

### SAFETY & DISPOSAL

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.



## PROPERTIES

<b>Chemical Base</b>	: Acrylic Dispersion
<b>Density</b>	: 1.44 ± 0.03 g/ml
<b>Color</b>	: Grey
<b>Waiting Time</b>	: 5-10 min. (20°C and 50% R.H.)
<b>Working Duration</b>	: 35-45 min. (20°C and 50% R.H.)
<b>Set to Traffic</b>	: 18-48 h (20°C and 50% R.H.)
<b>Full Setting</b>	: 48 h
<b>Application Temperature</b>	: +5°C to +35°C

## PACKAGING

20 kg plastic pail

## DISCLAIMER

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.