

SPRAY PAINT

1 - Description

Akfix Spray Paint; is a rapid-drying, solvent-based decorative product designed for use in many different application possibilities. It has a wide range of colors compatible with RAL.

2 - Properties

- Very good coverage
- Excellent adhesion on many surfaces
- Good flow, smooth surface
- Quick-drying
- Suitable for indoor and outdoor applications
- Polishable surface
- Weather-resistant, light-proof.
- Scratch-, shock- and impact-resistant
- Quick-drying (The drying time depends on surrounding temperature, air humidity and thickness of the applied coat).

3 - Application Areas

- Suitable for wood, metal, paper, glass or paintable hard plastics as well as for many textiles for any variety of designing applications.
- Also applicable for the designing of finery, concrete and natural stone.
- It can be used for hobby purposes.

4 - Product Information

Shelf Life	10 years
Storage Conditions	Cool and dry ambient between 10°C to +25°C max. 60% humidity

5 - Technical Data

Parameter	Conditions/Parameters	Value
Odor		Solvent
Base		Acrylic Based Aerosol Paint
Efficiency		Approx. 2 - 2,5m ² / 400 ml Can* Approx. 5 - 8 minutes (Dust-dry)
Drying Time	(20 °C and 50% R.H.)	Approx. 15 - 20 minutes (Dry to touch) Approx. 24 hours (Hardened)
Temperature Resistance		Up to 80°C

* Depending on consistence and color.

6 – Directions for Use

Art No	Color Code
Glossy Black	RAL 9005
Matte Black	RAL 9005
Glossy White	RAL 9003
Matte White	RAL 9003
Glossy Grey	RAL 7035
Glossy Red	RAL 3020
Glossy Machine Red	RAL 3002
Glossy Yellow	RAL 1003
Glossy Orange	RAL 2008
Glossy Purple	RAL 4005
Glossy Pink	RAL 4003
Glossy Green	RAL 6016
Moss Green	RAL 6005
Glossy Blue	RAL 5017
Glossy Cream	RAL 1015
Glossy Black	RAL 9005

7 – Standards

Meets or exceeds the requirements of the following specifications:

- **Environmentally compatibility:** The caps and packagings are made of recyclable material.
- **Disposal:** Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed of as "special refuse".
- **Marking/Labeling:** All products comply with the actual labelling regulations according to preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

8 – Directions for Use

- The surface has to be clean, dry and free from fat.
- Remove residues of old paintings and rust, then sand and prime if necessary.
- Let dry for 1 - 2 hours.
- Use Plastic Primer on plastic parts.
- Cover areas not to be painted.
- Before use, shake the can for 3 minutes.
- Test spray at an invisible spot to check colour-matching and compatibility of the lacquer.
- Spray from a distance of approx. 25 cm several thin coats.
- Do not spray over synthetic paints!

9 -Safety

Ensure good ventilation of the work station. Wear personal protective equipment. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Store in a well-ventilated place. Keep cool. Check MSDS guidelines for disposal and further information concerning safety. Keep out of reach of children.

10 -Disclaimer

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.